

HT SERIES



Features

Adopt super-quality alternating motor, which makes the piston move reciprocally in the cylinder and produce air flow that is large in output and high in pressure.

Non-oil lubricating design to produce purer compressed air.

Adopt aluminum alloy. The case is small in volume quick in heat-dissipation and east to move.

Phosphorize disposition, regular collaring and adhesive strength.

Application

It's widely used for planting aquarium plant, aerating for seafood in hotels, restaurants, seafood booths, and feeding pools etc. It's also used for air supply spare parts of food machine, medical instrument, belching paint, making and designing advertising lamp and new type LPG and LNG.

Notes

The products must be put above water level, avoid sunshine and rain.

Model	Voltage	Power	Pressure	Output	Weight	Dimensions
HT - 200	220V / 50HZ	20W	25kPA	1.8 m3/h	3.0 kg	230 x 140 x 150 mm
HT - 400	220V / 50HZ	30W	25kPA	2.4 m3/h	3.5 kg	258 x 168 x 179 mm
HT - 500	220V / 50HZ	50W	30kPA	3.5 m3/h	5.5 kg	266.5 x 165 x 220 mm
HT - 501	220V / 50HZ	50W	30kPA	2.8 m3/h	5.5 kg	224.5 x 165 x 200 mm
HT - 650	220V / 50HZ	65W	35kPA	4.5 m3/h	5.5 kg	226.5 x 165 x 220 mm
HT- 651	220V / 50HZ	65W	35kPA	3.4 m3/h	6.5 kg	224.5 x 165 x 216 mm



THONG FATT JAYA MACHINERY HARDWARE SDN. BHD.

同發機械五金有限公司 (176024-V)

775-779, Jalan Kuala Kangsar, Taman Tasek Jaya,
31400 Ipoh, Perak. Malaysia.
Tel: 00-605-5468 659, 5455 751, 5479 196, 5454 107
Fax: 00-605-5482 282, 5474 753
Email: tfjaya@tm.net.my / tfjaya@streamyx.com
Website: <http://www.thongfattjaya.com.my>