



# PORTABLE FIRE FIGHTING PUMP SET MODEL: PFP13



Petrol Engine	
Type	Forced Air-Cooled, 4-Stroke, OHV 25° Inclined Cylinder, 1-Cylinder
Bore x Stroke (mm)	88 x 64
Compression Ratio	8:1
Max. Power & Speed (HP/KW/rpm)	13 / 8.8 / 3600
Max. Torque & Speed (N.m./rpm)	26.5 / 2500
Ignition Method	Transistor Ignition
Starting Method	Electric Start / Manual Recoil Start
Water Pump	
Type	Single Stage, Single Suction Centrifugal Pump
Capacity (m <sup>3</sup> /h)	30
Head (m)	50
Max. Suction Height (m)	7
Inlet & Outlet Diameter (mm)	DN65
Total Weight Per Set (kg)	<75
Overall Dimensions (L x H x W) (mm)	630 x 525 x 590



**THONG FATT JAYA MACHINERY HARDWARE SDN. BHD.**

**同發機械五金有限公司** (176024-V)

775-779, Jalan Kuala Kangsar, Taman Tasek Jaya,  
31400 Ipoh, Perak, Malaysia.  
Tel: 00-605-5468 659, 5455 751, 5479 196, 5454 107  
Fax: 00-605-5482 282, 5474 753  
Email: tfjaya@tm.net.my / tfjaya@streamyx.com  
Website: <http://www.thongfattjaya.com.my>